

MY24 ELIMINATOR EURO 5

Starting At Rs.5,62,000 (Ex-Showroom)

GET ON-ROAD PRICE

(<https://kawasaki-india.com/on-road-price-estimator/>)

*Product pictures shown are for illustration purpose only.

*Actual product may vary from the picture shown here.

*Specification and pricing are subject to change.



AVAILABLE COLOURS

● METALLIC FLAT SPARK BLACK

Engine & Transmission	
TYPE	Liquid-cooled, 4-stroke Parallel Twin
DISPLACEMENT	451 cm ³
BORE AND STROKE	70.0 x 58.6 mm
COMPRESSION RATIO	11.3:1
VALVE SYSTEM	DOHC, 8 valves
FUEL SYSTEM	Fuel injection: ø32 mm x 2
FUEL TYPE / MINIMUM OCTANE RATING	-
IGNITION	Digital
STARTING	Electric
LUBRICATION	Forced lubrication, wet sump
TRANSMISSION	6-speed, return
MAXIMUM POWER	33.4 kW {45 PS} / 9,000 min ⁻¹
MAXIMUM POWER WITH RAM AIR	-
MAXIMUM TORQUE	42.6 N·m {4.3 kgf·m} / 6,000 min ⁻¹
ELECTRONIC RIDER AID	
Dimensions & Chassis	
FRAME TYPE	Trellis, high-tensile steel
RAKE / TRAIL	30° / 121 mm
TYRE - FRONT	130/70-18M/C 63H
TYRE - REAR	150/80-16M/C 71H
WHEELBASE	1,520 mm
GROUND CLEARANCE	150 mm
SEAT HEIGHT	735 mm
CURB MASS	176 kg
FUEL CAPACITY	13 litres

Dimensions & Chassis

OVERALL DIMENSIONS (L X W X H)

2,250 x 785 x 1,100 mm

Brakes & Suspension

FRONT / WHEEL TRAVEL

ø41 mm telescopic fork / 120 mm

REAR / WHEEL TRAVEL

Twin shocks / 90 mm

BRAKE - FRONT

ø310 mm disc

CALIPER - FRONT

Dual-piston

BRAKE - REAR

ø240 mm disc

CALIPER - REAR

Dual-piston